

The Life Support Communicator is a universal communication device that can be used with a 12V DC power supply. It is widely used for communication in Life Support Systems.

The unit has 6 connections for microphone / speaker sets in the back panel. The tender can work with the internal speaker/mic or use a headset if there is too much background noise.

The input microphone volume can be adjusted separately for each communication line.

It has been built into a 10" Isel mounting frame, which completely encloses the device. The unit is IP40 protected.

Specifications	
Power supply:	11-15 VDC
Power consumption: (mains power)	Max. 20 W
Fuse:	1.6 A (slow)
Operating temperature:	-25 / +50 °C
Dimensions: (incl. Knobs and connectors)	Height: 133 mm Width: 260 mm Depth: 280 mm
Weight:	3.4 Kg
Headset impedance tender:	Headphone: 8-32 Ohm Microphone: 8-600 Ohm
Headset impedance line 1-6	Speaker/headphone: 8-32 Ohm Microphone: 200-600 Ohm
Output power tender:	3 W
Output power Line 1-6:	6 x 3W



The 2006 Life Support Communicator



Hyperbaric Technology B.V.

Blijk 16 - 4941 SG - Raamsdonksveer - The Netherlands

☎ +31 (0)162 522202 ☎ +31 (0)162 519069

✉ hytech@hytech.nl 🌐 <http://www.hytech.nl>